

OIL & PRESSURE SPECIFICATIONS



OIL VOLUME AND PRESSURE				VOLUME	TOLERANCE
REVIVE / REVIVE MAX 125				36 ml	+/- 2 ml
REVIVE / REVIVE MAX 160				42 ml	+/- 2 ml
Druck (psi)					
REVIVE / REVIVE MAX 185	MIN	FACTORY	MAX	46 ml	+/- 2 ml
REVIVE / REVIVE MAX 213	250	→ 270	→ 300	55 ml	+/- 2 ml
REVIVE 272				18 ml	+/- 2 ml
DIVINE 125				46 ml	+/- 2 ml
DIVINE 160				52 ml	+/- 2 ml
Druck (psi)					
DIVINE 185	MIN	FACTORY	MAX	58 ml	+/- 2 ml
DIVINE SL / Rascal (all)	300	→ 370	→ 400	13 ml	+ 2 ml

OIL SPECIFICATIONS

ex works

[BikeYoke Sanquine hydraulic oil](#)

(viscosity 16 cSt @ 40°)

Suspension oils for bicycle components from other manufacturers with a similar viscosity can generally be used, but experience has shown that our droppers work best with the oil mix described above

GREASE FOR LOWER TUBE UNIT

ex works

[BikeYoke Dropper Goo](#)

Alternatives:

Buzzy's Slick Honey

Rock Shox Dynamic Grease

r.s.p. Slick Kick