

ÖL-VOLUMEN UND DRUCK				VOLUMEN	TOLLERANZ
REVIVE / REVIVE MAX 125				36 ml	+/- 2 ml
REVIVE / REVIVE MAX 160				42 ml	+/- 2 ml
REVIVE / REVIVE MAX 185				46 ml	+/- 2 ml
REVIVE / REVIVE MAX 213				55 ml	+/- 2 ml
REVIVE 272				18 ml	+/- 2 ml
DIVINE 125				46 ml	+/- 2 ml
DIVINE 160				52 ml	+/- 2 ml
DIVINE 185				58 ml	+/- 2 ml
DIVINE SL / Rascal (all)				13 ml	+ 2 ml

ÖL-SPEZIFIKATIONEN

Ab Werk

[BikeYoke Sanquine Hydrauliköl](#)

(96% MOBIL DTE 10 EXCEL 15 (viscosity 16 cSt @ 40°), 4% R.S.P. No Slip)

Suspension-Öle für Fahrradkomponenten anderer Hersteller mit ähnlicher Viskosität können in der Regel verwendet werden, allerdings funktionieren unsere Stützen erfahrungsgemäß am Besten mit dem oben beschriebenen Öl-Mix

FETT FÜR UNTERE ROHREINHEIT

Ab Werk

[BikeYoke Dropper Goo](#)

Alternativen:

Buzzy's Slick Honey
Rock Shox Dynamic Grease
r.s.p. Slick Kick

OIL VOLUME AND PRESSURE				VOLUME	TOLERANCE
REVIVE / REVIVE MAX 125				36 ml	+/- 2 ml
REVIVE / REVIVE MAX 160				42 ml	+/- 2 ml
Druck (psi)					
REVIVE / REVIVE MAX 185	MIN	FACTORY	MAX	46 ml	+/- 2 ml
REVIVE / REVIVE MAX 213	250	270	300	55 ml	+/- 2 ml
REVIVE 272				18 ml	+/- 2 ml
DIVINE 125				46 ml	+/- 2 ml
DIVINE 160				52 ml	+/- 2 ml
Druck (psi)					
DIVINE 185	MIN	FACTORY	MAX	58 ml	+/- 2 ml
DIVINE SL / Rascal (all)	300	370	400	13 ml	+ 2 ml
OIL SPECIFICATIONS					
ex works					
BikeYoke Sanquine hydraulic oil					
(96% MOBIL DTE 10 EXCEL 15 (viscosity 16 cSt @ 40°), 4% R.S.P. No Slip)					
Suspension oils for bicycle components from other manufacturers with a similar viscosity can generally be used, but experience has shown that our droppers work best with the oil mix described above					
GREASE FOR LOWER TUBE UNIT					
ex works					
BikeYoke Dropper Goo					
Alternatives:					
Buzzy's Slick Honey					
Rock Shox Dynamic Grease					
r.s.p. Slick Kick					