

BikeYoke compatibility chart

Spezialized Stumpjumper

| | BikeYoke model | |
|------------------|--------------------|--------------------|
| Bike model | SJ01 | SJ02 |
| 2010 26 | 190x45 | |
| 2011 26 | 190x45 | |
| 2011 26 EVO | 190x51** 190x45 | |
| 2011 29 | 190x45 | |
| 2012 26 | 190x51** 190x45 | |
| 2012 26 EVO | 190x51** 190x45 | |
| 2012 29 | 190x45 | |
| 2013 26 | 190x51** 190x45 | |
| 2013 26 EVO | 190x51** 190x45 | |
| 2013 29 | 190x45 | |
| 2013 29 EVO | 190x45 | |
| 2014 26 EVO | 190x51** 190x45 | |
| 2014 29 | 190x45 | |
| 2014 29 EVO | 190x45 | |
| 2014 650b EVO | 190x51** 190x45 | |
| 2015 29 | 190x45 | |
| 2015 29 EVO | 190x45 | |
| 2015 650b EVO | 190x51** 190x45 | |
| 2016 29 | | 190x51** 190x45 |
| 2016 650b | | 190x51** 190x45 |
| 2016 6Fatty | | 190x51** 190x45 |
| 2017 29 / 6Fatty | | 190x51** 190x45 |
| 2017 650b | | 190x51** 190x45 |
| 2018 29 / 6Fatty | | 190x51** 190x45 |
| 2018 650b | | 190x51** 190x45 |

ANNOTATIONS

| shock size in mm | equivalent in inch |
|------------------|--------------------|
| 190x51 | 7.5x2.0 |
| 190x45 | - |

All allowed combinations will create same geometry and travel as original, unless specified differently

rear wheel travel with 45mm stroke shocks might be slightly reduced

** rear wheel travel will increase by about 5mm

| |
|--|
| Standard shocks must have standard 12.7mm (1/2") diameter bushings and maximum 12.70mm eyelet width |
| Due to the numerously available shocks, please carefully check for sufficient clearance between tires, shock and frame parts in any position throughout the complete shock stroke, especially when bottoming out - frame or shocks parts must not collide in any position! |